



Drop-In Solid Filter Cartridges

- Max. pressure: 125 psi

Polypropylene cartridges capture and remove solid contaminants from water and industrial liquids. These one-piece, depth-type filters trap particulates throughout the filter structure. They fit compatible housings to provide filtration for process water, plating solutions, and chemical processing fluids.



Pentair/Pentek

Micron Rating	Outside Diameter	Inside Dia.	Maximum Temperature	Brand	4 7/8" H		9 7/8" H		10" H		20" H		30" H		40" H	
					Flow Rate	Item No.	Flow Rate	Item No.	Flow Rate	Item No.	Flow Rate	Item No.	Flow Rate	Item No.	Flow Rate	Item No.
1 micron	2 1/2"	1"	180 °F	Pentair/Pentek	—	—	—	—	—	—	10 gpm	—	—	—	—	—
	2 5/8"	1 1/8"	176 °F	3M	—	—	—	—	10 gpm	—	20 gpm	—	—	—	—	—
5 micron	2 5/8"	1 1/8"	145 °F	Pentair/Pentek	2 gpm	—	—	—	—	—	—	—	—	—	—	—
	2 5/8"	1 1/8"	175 °F	Pentair/Pentek	—	—	2 gpm	—	—	—	—	—	—	—	—	—
10 micron	2 1/2"	1"	180 °F	Pentair/Pentek	—	—	—	—	—	—	10 gpm	—	—	—	—	—
	2 5/8"	1 1/8"	176 °F	3M	—	—	—	—	10 gpm	—	20 gpm	—	—	30 gpm	—	40 gpm
25 micron	2 1/2"	1"	180 °F	Pentair/Pentek	—	—	—	—	5 gpm	—	10 gpm	—	—	—	—	—
	2 5/8"	1 1/8"	176 °F	3M	—	—	—	—	10 gpm	—	20 gpm	—	—	30 gpm	—	40 gpm
50 micron	2 5/8"	1 1/8"	176 °F	3M	—	—	—	—	10 gpm	—	20 gpm	—	—	30 gpm	—	40 gpm
75 micron	2 5/8"	1 1/8"	176 °F	3M	—	—	—	—	10 gpm	—	20 gpm	—	—	30 gpm	—	40 gpm